



/// 5 AXLE 59,000L MULTI-COMPT TC 406 SEMI-TRAILER (Ontario)



= 1 : 10 :::	DOTTOOCHACRE		
Technical Specification	PS55906NA6RE		
Model & Regulations	TC 406; ASME; CSA B620; CMVSS 121 (Brakes);	Hub & Drums for	Conmet Unimount ADI Hubs w/ Outboard
	CMVSS 108 (Electrical); ONT 413/O5 SPIF	All Suspensions	(Centrifuse) Brake Drums; Tiremaax Prep
Capacity & Compt	59,000L; 4, 5 & 6 Compartment Trailers;	Tridem Axle Wheels &	8.25 x 22.5 Std Aluminum Wheels;
	Double Bulkheads w/ Baffles per Design	Tires	Michelin XTE 11R 22.5 14(G)
Tank Outer Shell;	5454 H32 Alloy BTS Finish;	Lift & Steer Wheels	12.25 x 22.5 Std Aluminum Wheels;
Tank Framing	Alum Crossmembers & Outriggers per design	& Tires	Michelin X-Multiway HD L385/65R 22.5
SUPER TANKER PKG	SUPERTANKER 5 YEAR Limited Warranty on	Wabco Brake Syst.	16.5 x 7 ABS 4S/2M RSS Plus on Tridem Axle;
Extended Warranty	Dixon, Betts & FloTech Components	CMVSS 121	ABS 2S/1M per Lift Steer Axles
Manholes;	Betts 20" 406-98 PAF Relief Manholes,	Air Tanks &	All Aluminum Air Tanks per Design;
Vents	Betts AVT 3.5" ALTS Sequential Air Vapour Vents	Wiring	Colour-Coded Air Lines per SAE Std
Overfill Protection	FloTech Optic Top & Retain Sensors Per Compt	KP Plate	Heavy Duty 3/8" Steel Construction w/ 2"
	W/ On Board Monitor		King Pin & 3" Adjustable Bolt Holes
Emergency Valves &	Betts 4" Air Internal Valves w/ Tef-Sil Seals	Landing Gear	Holland Mark V 200,000 LBS Two Speed w/
Discharge System	Dixon 4" API Adaptors w/ Baylast Seals		Non-Removeable Handle
Vapour Recovery Syst.	Three 3" Vapour API w/ Poppets; 1 at Rear of	Paint	Susp Frame & Hangers Powder Coat Black;
Loading & Unloading	for Loading, 2 at Discharge Area for Unloading		Axle Tectyl Coat, LG Black Armour Coat
Piping System	4" Seamless Alum Sch 10 High Flow Piping	Electrical & Lighting	Fully Electrical and Lighting Systems. Truck-Lite
	Formed & Bent with Minimum Welding	Systems CMVSS 108	LED Lighting PKG
Suspension Frame	Heavy Duty HLSA Steel Suspension Frame	Aluminum Cabinets	42" Roadside Utility Cabinet;
	w/ Brackets for Huck Bolt-On Installation		48" Curbside Operation Cabinet
Suspension Tridem Axle	HENDRICKSON INTRAXX RH HXL-3 PKG AAT25K-14",	Other Accessories	Aluminum Fenders; Aluminum Ladder;
	25,000 LBS Capacity, Bolt-On Style		Aluminum Hose Tubes & More
Suspension Lift & Self-	Ingersol IMT-25K-14" TLS; 25,000 LBS Capacity	Documents	All Test & Certifications Documents
Steer Axles (2)	w/ Lift & Self Steer PKG		Completed & Provide to the Customer







