

/// 5 AXLE 59,000L MULTI-COMPT TC 406 SEMI-TRAILER (Michigan)



Technical Specification	PS55906NA6RE		
Model & Regulations	TC 406; ASME; CSA B620; CMVSS 121 (Brakes); CMVSS 108 (Electrical); ONT 413/O5 SPIF	Hub & Drums for All Suspensions	Conmet Unimount ADI Hubs w/ Outboard (Centrifuse) Brake Drums; Tiremaax Prep
Capacity & Compt	59,000L; 4, 5 & 6 Compartment Trailers; Double Bulkheads w/ Baffles per Design	Tridem Axle Wheels & Tires	8.25 x 22.5 Std Aluminum Wheels; Michelin XTE 11R 22.5 14(G)
Tank Outer Shell; Tank Framing	5454 H32 Alloy BTS Finish; Alum Crossmembers & Outriggers per design	Lift & Steer Wheels & Tires	12.25 x 22.5 Std Aluminum Wheels; Michelin X-Multiway HD L385/65R 22.5
SUPER TANKER PKG Extended Warranty	SUPERTANKER 5 YEAR Limited Warranty on Dixon, Betts & FloTech Components	Wabco Brake Syst. CMVSS 121	16.5 x 7 ABS 4S/2M RSS Plus on Tridem Axle; ABS 2S/1M per Lift Steer Axles
Manholes; Vents	Betts 20" 406-98 PAF Relief Manholes, Betts AVT 3.5" ALTS Sequential Air Vapour Vents	Air Tanks & Wiring	All Aluminum Air Tanks per Design; Colour-Coded Air Lines per SAE Std
Overfill Protection	FloTech Optic Top & Retain Sensors Per Compt W/ On Board Monitor	KP Plate	Heavy Duty 3/8" Steel Construction w/ 2" King Pin & 3" Adjustable Bolt Holes
Emergency Valves & Discharge System	Betts 4" Air Internal Valves w/ Tef-Sil Seals Dixon 4" API Adaptors w/ Baylast Seals	Landing Gear	Holland Mark V 200,000 LBS Two Speed w/ Non-Removeable Handle
Vapour Recovery Syst. Loading & Unloading	Three 3" Vapour API w/ Poppets; 1 at Rear of for Loading, 2 at Discharge Area for Unloading	Paint	Susp Frame & Hangers Powder Coat Black; Axle Tectyl Coat, LG Black Armour Coat
Piping System	4" Seamless Alum Sch 10 High Flow Piping Formed & Bent with Minimum Welding	Electrical & Lighting Systems CMVSS 108	Fully Electrical and Lighting Systems. Truck-Lite LED Lighting PKG
Suspension Frame	Heavy Duty HLSA Steel Suspension Frame w/ Brackets for Huck Bolt-On Installation	Aluminum Cabinets	42" Curbside Operation Cabinet; 48" Roadside Utility Cabinet
Suspension Tridem Axle	HENDRICKSON INTRAXX RH HXL-3 PKG AAT25K-14", 25,000 LBS Capacity, Bolt-On Style	Other Accessories	Aluminum Fenders; Aluminum Ladder; Aluminum Hose Tubes & More
Suspension Lift & Self-Steer Axles (2)	Ingersol IMT-25K-14" TLS; 25,000 LBS Capacity w/ Lift & Self Steer PKG	Documents	All Test & Certifications Documents Completed & Provide to the Customer