

/// 5 AXLE 63,000L MULTI-COMPT TC 406 B-TRAIN (CLOUD)



Technical Specification	PL33403NA6RE & PR2290XNA6RE		
Model & Regulations	TC 406; ASME; CSA B620; CMVSS 121 (Brakes) CMVSS 108 (Electrical); ONT 413/O5 SPIF	Hub & Drums for All Suspensions	Conmet Unimount ADI Hubs w/ Outboard (Centrifuse) Brake Drums; Tiremaax Prep
Capacity & Compt	63,000L; 4, 5 & 6 Compartment B-Train Double Bulkheads w/ Baffles per Design	Tandem & Tridem Axle Wheels & Tires	8.25 x 22.5 Std Aluminum Wheels Michelin XTE 11R 22.5 14(G)
Tank Outer Shell	5454 H32 Alloy BTS Finish	Wabco Brake Syst. CMVSS 121	ABS Wabco 2S/2M for the Lead & 2S/1M for the Pup
Tank Framing	Alum Crossmembers & Outriggers per design	Air Tanks & Wiring	All Aluminum Air Tanks per Design Colour-Coded Air Lines per SAE Std
SUPER TANKER PKG Extended Warranty	SUPERTANKER 5 YEAR Limited Warranty on Dixon, Betts & FloTech Components	KP Plate Lead	Heavy Duty 3/8" Steel Construction w/ 2" King Pin & 3" Adjustable Bolt Holes
Manholes & Vents	Betts 20" 406-98 PAF Relief Aluminum Manholes , Betts AVT 3.5" ALTS Sequential Air Vapour Vents	KP Plate Pup	Heavy Duty 3/8 Steel Construction w/2" Forged Recessed King Pin & 3" Adjust Bolt Holes
Overfill Protection	FloTech Optic Top & Retain Sensors Per Compt W/ On Board Monitor(s)	Landing Gear	JOST AX 100 Aluminum 160,000 LBS Two Speed w/Non-Removeable Handle, None on Pup
Emergency Valves & Discharge System	Betts 4" Air Internal Valves w/ Tef-Sil Seals Dixon 4" API Adaptors w/ Baylast Seals	Paint	Susp Frame & Hangers Powder Coat Black Axle Tectyl Coat, LG Black Armour Coat
Vapour Recovery Syst. Loading & Unloading	Three 3" Vapour API w/ Poppets; 1 at Rear of for Loading, 2 at Discharge Area for Unloading	Electrical & Lighting Systems CMVSS 108	Fully Electrical and Lighting Systems. Truck-Lite LED Lighting PKG
Piping System	4" Seamless Alum Sch 10 High Flow Piping Formed & Bent with Minimum Welding	Aluminum Cabinets	48" Curbside Operation Cabinet on Lead 42" Curbside Operation Cabinet on Pup
Suspension Frame	Heavy Duty HLSA Steel Suspension Frames w/ Brackets for Huck Bolt-On Installation	Other Accessories	Aluminum Fenders, No Ladder Aluminum Hose Tubes & More
Suspension Tridem & Tandem Axle	HENDRICKSON INTRAXX RH HXL-3 PKG AAT25K-14", 25,000 LBS Capacity, Bolt-On Style	Documents	All Test & Certifications Documents Completed & Provide to the Customer
5th Wheel	Holland Kompensator FW35 w/Remote Grease Manifold		