

/// 5 AXLE 61,000L MULTI-COMPT TC 406 B-TRAIN



| | | | |
|--|---|--|--|
| Specification Sheet | PL33303NA6RE & PR2280XNA6RE | | |
| Model & Regulations | TC 406; ASME; CSA B620; CMVSS 121 (Brakes) CMVSS 108 (Electrical); ONT 413/O5 SPIF | Hub & Drums for All Suspensions | Conmet Unimount ADI Hubs w/ Outboard (Centrifuse) Brake Drums; Tiremaxx Prep |
| Capacity & Compt | 61,000L; 4, 5 & 6 Compartment B-Train Double Bulkheads w/ Baffles per Design | Tandem & Tridem Axle Wheels & Tires | 8.25 x 22.5 Std Aluminum Wheels Michelin XTE 11R 22.5 14(G) |
| Tank Outer Shell Tank Framing | 5454 H32 Alloy BTS Finish Alum Crossmembers & Outriggers per design | Wabco Brake Syst. CMVSS 121 | ABS Wabco 2S/2M for the Lead & 2S/1M for the Pup |
| SUPER TANKER PKG Extended Warranty | SUPERTANKER 5 YEAR Limited Warranty on Dixon, Betts & Flotech Components | Air Tanks & Wiring | All Aluminum Air Tanks per Design Colour-Coded Air Lines per SAE Std |
| Manholes & Vents | Betts 20" 406-98 PAF Relief Manholes, Betts AVT 3.5" ALTS Sequential Air Vapour Vents | KP Plate Lead | Heavy Duty 3/8" Steel Construction w/ 2" King Pin & 3" Adjustable Bolt Holes |
| Overfill Protection | Flotech Optic Top & Retain Sensors Per Compt W/ On Board Monitor | KP Plate Pup | Heavy Duty 3/8" Steel Construction w/2" Forge Recessed King Pin & 3" Adjust Bolt Holes |
| Emergency Valves & Discharge System | Betts 4" Air Internal Valves w/ Tef-Sil Seals Dixon 4" API Adaptors w/ Baylast Seals | Landing Gear | Holland Mark V 200,000 LBS Two Speed w/ Non-Removeable Handle |
| Vapour Recovery Syst. Loading & Unloading | Three 3" Vapour API w/ Poppets; 1 at Rear of for Loading, 2 at Discharge Area for Unloading | Paint | Susp Frame & Hangers Powder Coat Black Axle Tectyl Coat, LG Black Armour Coat |
| Piping System | 4" Seamless Alum Sch 10 High Flow Piping Formed & Bent with Minimum Welding | Electrical & Lighting Systems CMVSS 108 | Fully Electrical and Lighting Systems. Truck-Lite LED Lighting PKG |
| Suspension Frame | Heavy Duty HLSA Steel Suspension Frame w/ Brackets for Huck Bolt-On Installation | Aluminum Cabinets | 48" Curbside Operation Cabinet on Lead 42" Curbside Utility Cabinet on Pup |
| Suspension Tridem & Tandem Axle | HENDRICKSON INTRAXX RH HXL-3 PKG AAT25K-14", 25,000 LBS Capacity, Bolt-On Style | Other Accessories | Aluminum Fenders, Aluminum Ladders (2), Aluminum Hose Tubes & More |
| 5th Wheel | Holland Kompensator FW35 w/Remote Grease Manifold | Documents | All Test & Certifications Documents Completed & Provide to the Customer |